

# MATERIAL SAFETY DATA SHEET

MSDS DATE: 03/11/08

FILE NO.: ALX-380-059

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

**PRODUCT NAME:** Hygromycin B (liquid)  
**SYNONYMS:** N/A  
**PRODUCT CODES:** ALX-380-059

**MANUFACTURER:** ALEXIS Corporation  
**ADDRESS:** Industriestrasse 17  
CH-4415 Lausen  
Switzerland

**TELEPHONE:** +41 61 926 8989  
**FAX PHONE:** +41 61 926 8979  
**WEBSITE:** www.axxora.com

---

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>Formula:</u>	<u>CAS #</u>	<u>EC #</u>	<u>Annex I Index #</u>
C <sub>20</sub> H <sub>37</sub> N <sub>3</sub> O <sub>13</sub>	31282-04-9	N/A	N/A

---

## SECTION 3: HAZARDS IDENTIFICATION

---

**ACUTE HEALTH EFFECTS:** TOXIC by inhalation, ingestion, or skin absorption.

---

## SECTION 4: FIRST AID MEASURES

---

**EYES:** Rinse immediately with plenty of water for 15 minutes. Check for and remove any contact lenses. Seek medical attention if symptoms appear.

**SKIN:** Wash immediately with water for 15 minutes. Remove contaminated clothing. Seek medical attention if symptoms appear.

**INGESTION:** Rinse mouth with water. Do not induce vomiting. Seek medical attention if symptoms appear. Provide MSDS and label information if possible.

**INHALATION:** Take into fresh air. If breathing is difficult, administer oxygen. Get medical attention.

---

## SECTION 5: FIRE FIGHTING MEASURES

---

**EXTINGUISHING MEDIA:** Water spray, water foam, polymer foam, carbon dioxide, dry chemicals.

**SPECIAL FIRE FIGHTING PROCEDURES:** In case of fire, watch out for the formation of toxic smoke and gases. Wear self-contained respiration equipment. Prevent contact with skin and eyes.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** May be combustible at high temperatures.

**HAZARDOUS DECOMPOSITION PRODUCTS:** N/A

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**PERSONAL PRECAUTIONS:** Evacuate area. Wear respirator, chemical safety goggles, rubber boots and heavy rubber gloves.

**ACCIDENTAL RELEASE MEASURES:** Avoid formation of dust, sweep up spill and place in sealed container and hold for disposal. Ventilate area and wash spill site after material pickup is complete.

---

## SECTION 7: HANDLING AND STORAGE

---

**HANDLING AND STORAGE:** Keep locked up. Keep away from heat, sources of ignition and incompatibles such as oxidizing agents. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Avoid contact with skin and eyes; do not breathe dust. Avoid prolonged or repeated exposure. Immediately remove all contaminated clothing. Wash hands before breaks and after work. Avoid eating, drinking and storage of food in the work room. Store tightly sealed at +4°.

# MATERIAL SAFETY DATA SHEET

MSDS DATE: 03/11/08

FILE NO.: ALX-380-059

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**ENGINEERING CONTROLS:** Use only in chemical fume hood. Safety shower and eye bath.  
**VENTILATION:** Government approved respirator.  
**EYE PROTECTION:** Chemical safety goggles.  
**SKIN PROTECTION:** Compatible gloves, protective coat or clothing.  
**SECTION 8 NOTES:** Wash thoroughly after handling. Wash contaminated clothing before reuse.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Dark brown solution.  
**ODOR:** N/A  
**pH AS SUPPLIED:** N/A  
**BOILING POINT:** N/A  
**MELTING POINT:** N/A  
**FREEZING POINT:** N/A  
**VAPOR PRESSURE (mmHg):** N/A  
**VAPOR DENSITY (AIR = 1):** N/A  
**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** N/A  
**EVAPORATION RATE:** N/A  
**BASIS (=1):** N/A  
**SOLUBILITY:** N/A  
**MOLECULAR WEIGHT:** 527.5

---

## SECTION 10: STABILITY AND REACTIVITY

---

**STABILITY:** Stable. Avoid strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION:** Carbon monoxide, carbon dioxide, nitrogen oxides.  
**HAZARDOUS POLYMERIZATION:** Will not occur.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

**RTECS # :** WK2130000

**TOXICOLOGICAL INFORMATION:** TOXIC. Harmful by inhalation, ingestion, or skin absorption. Risk of serious damage to eyes. May cause sensitization by inhalation and skin contact. May be irritating to mucous membranes and upper respiratory tract. Repeated exposure can cause hearing loss. Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting. Exposure can cause Conjunctivitis, dermatitis. Target organ is the ear.  
To the best of our knowledge, the toxicological properties have not been thoroughly investigated.

**LD<sub>50</sub>:** Mouse [Oral]: 46000 units/kg  
Mouse [Intravenous]: 6 mg/kg  
Rat [Inhalation]: 2.22 mg/m<sup>3</sup>  
Rat [Intraperitoneal]: 63 mg/kg  
Guinea Pig [Intraperitoneal]: 13 mg/kg

**LD<sub>Lo</sub>** Mouse [Intraperitoneal]: 6 mg/kg

**CHRONIC EXPOSURE:** Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

**CHRONIC EXPOSURE-CARCINOGEN:** Not available.

**CHRONIC EXPOSURE-MUTAGEN:** Not available.

**CHRONIC EXPOSURE-TERATOGEN:** Not available.

# MATERIAL SAFETY DATA SHEET

MSDS DATE: 03/11/08

FILE NO.: ALX-380-059

---

## SECTION 12: ECOLOGICAL INFORMATION

---

ECOLOGICAL INFORMATION: N/A

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL METHOD: Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations.

---

## SECTION 14: TRANSPORT INFORMATION

---

### INTERNATIONAL TRANSPORT REGULATIONS:

**LAND – ROAD/RAILWAY:** ADR/RID: UN#: 2810  
Class: 6.1  
PG: I  
Proper Shipping Name: Toxic liquid, organic, n.o.s. (PCDDs and PCDFs)

**SEA:** IMDG: UN#: 2810  
Class: 6.1  
PG: I  
Proper Shipping Name: Toxic liquid, organic, n.o.s.  
Marine Pollutant: No  
Severe Marine Pollutant: No  
Technical Name: Required

**AIR:** IATA-DGR: UN#: 2810  
Class: 6.1  
PG: I  
Proper Shipping Name: Toxic liquid, organic, n.o.s.  
Inhalation Packing Group I: No  
Technical Name: Required

**SPECIAL PROVISIONS FOR TRANSPORT:** N/A

---

## SECTION 15: REGULATORY INFORMATION

---

### CLASSIFICATION AND LABELING ACCORDING TO EU DIRECTIVES:

**SYMBOL OF DANGER:** T, toxic

**R-PHRASES:** R26/27/28 - Very toxic by inhalation, in contact with skin and if swallowed.  
R41 - Risk of serious damage to eyes  
R42/43 - May cause sensitization by inhalation and skin contact.

**S-PHRASES:** S7 - Keep container tightly closed.  
S23 - Do not breathe vapor.  
S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S28 - After contact with skin, wash immediately with plenty of water.  
S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.  
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**U.S. FEDERAL REGULATIONS:** Not available.

**HCS CLASSIFICATION:** Not available.

**WHMIS (CANADA):** Not available.

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product

# MATERIAL SAFETY DATA SHEET

FILE NO.: ALX-380-059

MSDS DATE: 03/11/08

with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Alexis Corporation shall not be held liable for any damage resulting from handling or from contact with the above product.

For R&D use only. Not for drug, household or other uses.